



REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	CABLE LENGTH
P1	1	+3.3V	ORANGE	20	MOLEX 39-01-2240 or EQUIV.	350±15mm
	2	+3.3V	ORANGE	20		
	3	COM	BLACK	20		
	4	+5V	RED	20		
	5	COM	BALCK	20		
	6	+5V	RED	20		
	7	COM	BALCK	20		
	8	PW-OK	GRAY	22		
	9	+5Vsb	PURPLE	20		
	10	+12V	YELLOW	20		
	11	+12V	YELLOW	20		
	12	+3.3V	ORANGE	20		
	13	+3.3V	ORANGE	20		
	13	+3.3Vsense	BROWN	22		
	14	-12V	BLUE	22		
	15	COM	BALCK	20		
	16	PS-ON	GREEN	22		
	17	COM	BALCK	20		
	18	COM	BALCK	20		
	19	COM	BALCK	20		
20						
21	+5V	RED	20			
22	+5V	RED	20			
23	+5V	RED	20			
24	COM	BALCK	20			
P2	1	COM	BALCK	20	MOLEX 39-01-2080 or EQUIV.	350±15mm
	2	COM	BALCK	20		
	3	COM	BALCK	20		
	4	COM	BALCK	20		
P3	5	+12V	YELLOW	20		
	6	+12V	YELLOW	20		
PA	7	+12V	YELLOW	20	WST P4-A10202 or EQUIV.	350±15mm
	8	+12V	YELLOW	20		
	1	+12V	YELLOW	20		
	2	COM	BALCK	20		
PB	2	COM	BALCK	20	WST P4-A10202 or EQUIV.	155±10mm
	3	COM	BALCK	20		
	4	+5V	RED	20		
	4	+5V	RED	20		
PC	1	+5V	RED	22	AMP 171822-4 or EQUIV.	155±10mm
	2	COM	BALCK	22		
	3	COM	BALCK	22		
	4	+12V	YELLOW	22		
PD	1	+3.3V	ORANGE	20	MOLEX SD-67926-0311 or EQUIV.	350±15mm
	2	COM	BALCK	20		
PF	3	+5V	RED	20		
	4	COM	BALCK	20		
	5	+12V	YELLOW	20		
PE	1	+3.3V	ORANGE	20	MOLEX SD-67582-001 or EQUIV.	155±10mm
	2	COM	BALCK	20		
	3	+5V	RED	20		
PG	4	COM	BALCK	20		
	5	+12V	YELLOW	20		

P/N.:9PA500CB00

NOTE:
 1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
 2. 3. 公差: .XX±0.5 [0.02]、.XXX±0.25 [0.01]

UNIT:mm

MODEL NO. : FSP500-50FDB(STD0001)		TITLE: ASSY	SHEET: 1 OF 1	REV:01
R&D(2)	PE	DRAWN	DATE	
		樂家龍	Jun.22.2018	
INTERIOR COUNTERSIGN:				